


## HAZARD RATING

4-EXTREME  
3-HIGH  
2-MODERATE  
1-SLIGHT



## MATERIAL SAFETY DATA SHEET

(Prepared according to 29 CFR 1910. 1200)

Date Prepared: 6-4-07

**SECTION 1 - PRODUCT IDENTIFICATION**

Company Name	Steam Way International, Inc.	Emergency Telephone No.	1-800-535-5053
Address	4550 Jackson St., Denver, CO 80216	Information Telephone No.	303-355-3566
Product Name / ID#	FabriCover II (60564)	Product Type	Fabric Proectant <input checked="" type="checkbox"/> Proprietary Product

**SECTION 2 - HAZARDOUS INGREDIENTS**

Chemical Name/Common Name	Gas No.	Percent (optional)	TLV (Source)
Naphtha, Petroleum	8030-30-6	< 100 %	100 ppm (ACGIH) 500 ppm (OSHA-PEL)

\* Substances  Contains no substances - subject to the reporting requirements of SARA 313 and 40 CFR Part 372.

**SECTION 3 - PHYSICAL DATA**

Boiling Point (°F)	>315°F	Specific Gravity (H <sub>2</sub> O=1.0)	0.772 ± 0.005	pH	NA	% VOC (ww)	95 %
Solubility In Water	<input type="checkbox"/> Complete <input checked="" type="checkbox"/> Insoluble	<input type="checkbox"/> Emulsifiable or (Dispersible)	<input type="checkbox"/> Slight (or Partial)				
Evaporation Rate (vs H <sub>2</sub> O)	<input checked="" type="checkbox"/> Faster <input type="checkbox"/> Slower <input type="checkbox"/> About the Same	Vapor Pressure	3.00	Vapor Density	4.70		
Appearance and Odor	Clear, colorless liquid. Solvent type odor.						

**SECTION 4 - FIRE AND EXPLOSION HAZARD DATA**

Flash Point (T.C.C.)	105°F	<input type="checkbox"/> None to boiling	Flammable Limits	Upper	NE	Lower	NE
Extinguishing Media	Dry chemical, foam or carbon dioxide.						
Special Fire Fighting Procedures	Use water spray to cool fire exposed containers. Wear self-contained breathing apparatus.						
Unusual Fire Explosion Hazards	None						

**SECTION 5 - REACTIVE DATA**

Stability	Stable	Incompatibility	Avoid strong oxidizing & reducing agents.				
Hazardous Decomposition Products	Combustion may yield Carbon Monoxide and/or Carbon Dioxide.						

**SECTION 6 - HEALTH HAZARDS**

Threshold Limit Value Product See Section 2 for Ingredients TLV	<input checked="" type="checkbox"/> None Established <input type="checkbox"/> Not Applicable	Primary routes of Exposure	<input checked="" type="checkbox"/> Eyes <input checked="" type="checkbox"/> Skin <input checked="" type="checkbox"/> Oral <input checked="" type="checkbox"/> Inhalation
Signs Symptoms of Over-exposure (Acute)	May cause mild eye irritation. Causes skin irritation. Breathing high concentrations of vapors may cause irritation of the nose, throat and signs of nervous system depression (i.e. headache, dizziness,etc).		
	Ingestion of excessive quantities may cause irritation of the digestive tract.		
Signs Symptoms of Over-exposure (Chronic)	Unknown		
Medical Conditions Aggravated by Over-exposure	Pre-existing skin & lung disorders.		
Carcinogen/Suspected Carcinogen Ingredients:	<input type="checkbox"/> NTP <input type="checkbox"/> IARC <input type="checkbox"/> OSHA <input checked="" type="checkbox"/> None		

**SECTION 7 - FIRST AID PROCEDURES - (If any Condition persists - Consult a physician.)**

Eyes	Flush with water for 15 minutes.
Skin	Wash affected area with plenty of soap & water for 5-10 minutes. Remove contaminated clothing and wash before reuse.
Ingestion	Do NOT induce vomiting or give anything by mouth as possibility of product reaching the lung and causing damage.
Inhalation	If qualified, give oxygen or artificial respiration as needed and/or seek medical help.

**SECTION 8 - SPECIAL PROTECTION INFORMATION**

Respiratory Protection	If concentration exceeds exposure limit, use NIOSH approved respirator for organic vapors.		
Ventilation requirements	<input checked="" type="checkbox"/> Local Exhaust <input checked="" type="checkbox"/> Mechanical	To keep below any listed TLV's and/or for general good ventilation.	
Protective Gloves	Rubber	Eye Protection	Safety glasses or goggles
Other Protective Clothing	Other impervious clothing should be worn as needed to prevent skin contact.		

**SECTION 9 - SPILL OR LEAK PROCEDURES**

Steps to be Taken if Released or Spilled	Dike area to contain spill. Absorb material into appropriate absorbent material.		
Waste Disposal Methods	Place in D.O.T. approved drum. Check all government regulations for disposal.		

**SECTION 10 - STORAGE AND HANDLING INFORMATION**

Precautions to be Taken in handling and Storage	Store in well ventilated, cool area in tightly closed containers. Keep out of reach children. Wash thoroughly after handling.		
---	---	--	--