
HAZARD RATING
4-EXTREME
3-HIGH
2-MODERATE
1-SLIGHT
0-INSIGNIFICANT



MATERIAL SAFETY DATA SHEET

(Prepared according to 29 CFR 1910. 1200)

Date Prepared: 2-15-12

SECTION 1 - PRODUCT IDENTIFICATION				
ompany Name Steam Way International, Inc.		Emergency Telephone No. 800-535-5053		
ldress P.O. Box 514, Jackson, WY 83001		Information Telephone No. 800-447-8326		
Product Name / ID# Extraction Power HP (1124)	Product Typ	e Carpe	t Extractor / Sanitizer	X Proprietory Product
SECTION 2 - HAZARDOUS INGREDIENTS				
Chemical Name/Common Name	Cas No		Percent (optional)	TLV (Source)
Alkyl (50% C ₁₄ , 40% C ₁₂ , 10% C ₁₆)				
dimethyl benzyl ammonium chloride	68424-85-1		< 3%	NA
Ethanol	64-17-5		< 1%	1000ppm (ACGIH)
* Substances X Contains no substances - subject to the reporting requirements of SARA 313 and 40 CFR Part 372.				
SECTION 3 - PHYSICAL DATA				
Boiling Point (°F) 212°F Specific Gravity (H ₂ O=1.0) 1.0444 ± 0.005 PH 11.0 ± 0.5 % VOC (ww) 0.59%				
Solubility In Water X Complete Insoluble Emulsifiable or (Dispersible) Slight (or Partial)				
Evaporation Rate (vs H ₂ O) Faster Slower X About the Same Vapor Pressure NE Vapor Density NE				
Appearance and Odor Clear, thin yellow liquid. Lemon odor.				
SECTION 4 - FIRE AND EXPLOSION HAZARD DATA				
Flash Point (T.C.C.) None to boiling Flammable Limits Upper NE Lower NE				
Extinguishing Media NA				
Special Fire Fighting Procedures NA				
Unusual Fire Explosion Hazards None				
SECTION 5 - REACTIVE DATA				
Stability Stable Incompatibility Anionics				
Hazardous Decomposition Products Thermal decomposition may produce toxic fumes of hydrogen chloride and oxides of carbon and nitrogen.				
SECTION 6 - HEALTH HAZARDS				
Threshold Limit Value Product See Section 2 for Ingredients TLV None Established Not Applicable Primary routes of Exposure X Eyes X Skin X Oral X Inhalation				
Signs Symptoms of Over-exposure (Acute) Causes eye irritation. May be irritating to the skin. Vapors or mist may cause irritation				
of mucous membranes. May be harmful if swallowed.				
Note to physician: Probable mucosal damage may contraindicate the use of gastric lavage.				
Signs Symptoms of Over-exposure (Chronic) Unknown				
Medical Conditions Aggravated by Over-exposure Unknown				
Carcinogen/Suspected Carcinogen Ingredients:			NTP IARC	OSHA X None
SECTION 7 - FIRST AID PROCEDURES - (If any Condition persists - Consult a physician.)				
Eyes Immediately flush with water for at least 15 minutes while holding eyelids open. Call a physician.				
Skin Immediately wash with water for at least 15 minutes. Remove any contaminated clothing and wash before reuse.				
Ingestion Drink a large quantity of water. Avoid alcohol. Call a physician immediately.				
Inhalation Remove to fresh air. If qualified, give artificial respiration or oxygen as necessary.				
SECTION 8 - SPECIAL PROTECTION INFORMATION				
Respiratory Protection None normally required.				
Ventilation requirements XLocal Exhaust XMechanical To keep below any listed TLV's and/or for general good ventilation.				
Protective Gloves Rubber Eye Protection Safety glasses or goggles				
Other Protective Clothing Chemical apron if splashing is anticipated or when handling large volume of material.				
SECTION 9 - SPILL OR LEAK PROCEDURES				
Steps to be Taken if Released or Spilled Contain spill. Absorb on clay or rags. Do not contaminate water, food or feed.				
Waste Disposal Methods Open dumping is prohibited. Check all government regulations relating to pesticides.				
SECTION 10 - STORAGE AND HANDLING INFORMATION				
Precautions to be Taken in handling and Storage Do not reuse empty container. Triple rinse (or equivalent). Wash thoroughly				
after handling. Keep out of reach of children. Store between 50-120°F.				