
HAZARD RATING
4-EXTREME
3-HIGH
2-MODERATE
1-SLIGHT
0-INSIGNIFICANT



MATERIAL SAFETY DATA SHEET

(Prepared according to 29 CFR 1910. 1200)

Date Prepared: 5-16-12

SECTION 1 - PRODUCT IDENTIFICATION				
Company Name Steam Way International, Inc.		Emergency Telephone No. 800-535-5053		
dress P.O. Box 514, Jackson, WY 83001		Information Telephone No. 800-447-8326		
Product Name / ID# Upholstery Prespray (1178)	Product Type Upholstery Prespray X Proprietory Product		X Proprietory Product	
SECTION 2 - HAZARDOUS INGREDIENTS				
Chemical Name/Common Name	Cas No.		Percent (optional)	TLV (Source)
*Diethylene glycol methyl ether	111-77-3		< 10%	NE
D'Limonene	5989-27-5		< 5%	NA
Ethanolamine	141-43-5		< 2%	
X * Substances Contains no substances - subject to the reporting requirements of SARA 313 and 40 CFR Part 372.				
SECTION 3 - PHYSICAL DATA				
Boiling Point (°F) 150°F Specific Gravity (H ₂ O=1.0) 1.014 ± 0.005 PH 9-10 % VOC (ww) 3%				
Solubility In Water				
Evaporation Rate (vs H ₂ O)				
Appearance and Odor Clear, light amber liquid. Citrus, slight glycol odor.				
SECTION 4 - FIRE AND EXPLOSION HAZARD DATA				
Flash Point (T.C.C.) over 120°F None to boiling Flammable Limits Upper NE Lower NE				
Extinguishing Media Water fog, Foam, CO² (Carbon Dioxide), Dry Chemical.				
Special Fire Fighting Procedures Water stream may spread fire - use water spray only to cool containers exposed to fire.				
Unusual Fire Explosion Hazards NA				
SECTION 5 - REACTIVE DATA				
Stability Stable Incompatibility Strong oxidizing agents. Acids.				
Hazardous Decomposition Products May produce oxide of carbon on burning.				
SECTION 6 - HEALTH HAZARDS				
Threshold Limit Value Product See Section 2 for Ingredients TLV None Established Not Applicable Primary routes of Exposure X Eyes X Skin X Oral X Inhalation				
Signs Symptoms of Over-exposure (Acute) May cause severe eye irritation. Frequent or prolonged contact may irritate the skin and				
cause dermatitis. Ingestion may cause nausea, vomiting and diarrhea. Excessive inhalation may cause headache or dizziness.				
Signs Symptoms of Over-exposure (Chronic) NA				
Medical Conditions Aggravated by Over-exposure May aggravate an existing dermatitis condition.				
Carcinogen/Suspected Carcinogen Ingredients:			NTP IARC	OSHA X None
SECTION 7 - FIRST AID PROCEDURES - (If any Condition persists - Consult a physician.)				
Eyes Flush with large amounts of water for 15 minutes.				
Skin Remove contaminated clothes and wash before reuse. Wash contaminated areas with plenty of water (or soap and water).				
Ingestion Do NOT induce vomiting. Drink large quantities of water to dilute contents in stomach. Contact a physician.				
Inhalation Remove to fresh air.				
SECTION 8 - SPECIAL PROTECTION INFORMATION				
Respiratory Protection None normally required if good ventilation maintained. Otherwise use organic vapors respirator.				
Ventilation requirements XLocal Exhaust Mechanical As needed to keep below any listed TLV or for general good ventilation.				
Protective Gloves Neoprene Eye Protection Safety goggles.				
Other Protective Clothing Chemical apron when handling large volumes of material.				
SECTION 9 - SPILL OR LEAK PROCEDURES				
Steps to be Taken if Released or Spilled Contain spill. May be soaked up with compatible absorbent materials.				
Waste Disposal Methods Observe all federal, state and local health and environmental regulations.				
SECTION 10 - STORAGE AND HANDLING INFORMATION				
Precautions to be Taken in handling and Storage Store in cool area away from acid and sources of ignition. Store so as to be				
inaccessible to children. Wash thoroughly after handling.				